



BDW Marine LLP  
Units 1 & 2 Poplars Farm  
Aythorpe Roding  
Dunmow  
Essex CM16 1RY

Tel: 01884 220016  
Fax: 0845 280 2195  
Email: enquiries@Premier-Paints.co.uk

## **TECHNICAL DATA SHEET**

### **PREMIER CLASSIC YACHT VARNISH - REF: - 53L644**

A quality traditional high gloss finish. Flexible with excellent UV and scratch resistance. Good flow for easy application. suitable for interior & exterior in most industrial/commercial and marine environments, where 2 coats give optimum performance.

<b>PACKAGE SIZE</b>	<b>1 Litre.</b>
<b>COLOUR</b>	<b>Clear</b>
<b>FLASH POINT</b>	<b>Above 32°C</b>
<b>DRYING TIME @ 20°C</b>	<b>Surface Dry: 4 - 6 hrs</b>
<b>VOLUME SOLIDS</b>	<b>48% (+/- 2%)</b>
<b>RECOMMENDED W.F.T.</b>	<b>120 microns</b>
<b>RECOMMENDED D.F.T.</b>	<b>58 microns</b>
<b>THEORETICAL SPREADING RATE</b>	<b>8 Sq. Metres/Litre</b>
<b>THINNERS</b>	<b>No. 2</b>
<b>SHELF LIFE</b>	<b>12 mths</b>
<b>V.O.C.</b>	<b>395 g/litre</b>

#### **SURFACE PREPERATION**

Ensure surface is free from rust, moisture, oil or other surface contamination.

When applying over previously varnish wood ensure the surface is clean and sand smooth. After sanding ensure all sanding dust is removed and wipe down with thinners. If the previously varnished wood is in poor condition then we recommend removing all previous coats.

When applying to bare wood sand smooth and remove any dust and wipe down with thinners. The first coat by be thinned by 10 % using Thinners No. 2



BDW Marine LLP  
Units 1 & 2 Poplars Farm  
Aythorpe Roding  
Dunmow  
Essex CM16 1RY

Tel: 01884 220016  
Fax: 0845 280 2195  
Email: [enquiries@Premier-Paints.co.uk](mailto:enquiries@Premier-Paints.co.uk)

### **APPLICATION**

**Brush or Roll and for best results lightly sand between coats using a fine 320 – 400 grade/grit paper.**

**Do not apply in temperatures below 5 c and ensure that the substrate temperature is above 5 c**

**Avoid applying late in the day as temperatures drop to allow the varnish to dry without the risk of condensation forming. Condensation will result in a loss of gloss finish.**

### **HEALTH & SAFETY**

**Refer to M.S.D.S. prior to use.**

**Provide adequate ventilation. Prolonged skin contact inhalation of vapour must be avoided.**

**Eye contamination - Flush with eyewash or warm water for 10 mins. Clean hands after use.**

**Any person or company using this product without first making enquiries as to the suitability for the intended purpose does so at their own risk, and Fiesta Industrial Paints Ltd can accept no liability for the performance of the product or for any loss or damage arising out of such use.**